



Standard Symbol

BMP Objectives

- Soil Stabilization
- Sediment Control
- Tracking Control
- Wind Erosion Control
- Non-Storm Water Management
- Materials and Waste Management

Definition and Purpose

These are procedures and practices for use of construction material in a manner that minimizes or eliminates the discharge of these materials to the storm drain system or to watercourses.

Appropriate Applications

This BMP applies to all construction projects. These procedures apply when the following materials are used or prepared on site:

■ Hazardous chemicals such as:

Acids,
lime,
glues,
adhesives,
paints,
solvents, and
curing compounds.

- Soil stabilizers and binders.
- Fertilizers.
- Detergents.
- Plaster.
- Petroleum products such as fuel, oil, and grease.
- Asphalt and concrete components.
- Pesticides and herbicides.
- Other materials that may be detrimental if released to the environment.

- | | |
|-------------------------------------|--|
| Limitations | ■ Safer alternative building and construction products may not be available or suitable in every instance. |
| Standards and Specifications | <ul style="list-style-type: none">■ Material Safety Data Sheets (MSDS) shall be supplied to the Resident Engineer (RE) for all materials.■ Latex paint and paint cans, used brushes, rags, absorbent materials, and drop cloths, when thoroughly dry and are no longer hazardous, may be disposed of with other construction debris.■ Do not remove the original product label, it contains important safety and disposal information. Use the entire product before disposing of the container.■ Mix paint indoors, or in a containment area. Never clean paintbrushes or rinse paint containers into a street, gutter, storm drain or watercourse. Dispose of any paint thinners, residue and sludge(s), that cannot be recycled, as hazardous waste.■ For water-based paint, clean brushes to the extent practical, and rinse to a drain leading to a sanitary sewer where permitted, or into a concrete washout pit. For oil-based paints, clean brushes to the extent practical and filter and reuse thinners and solvents.■ Use recycled and less hazardous products when practical. Recycle residual paints, solvents, non-treated lumber, and other materials.■ Use materials only where and when needed to complete the construction activity. Use safer alternative materials as much as possible. Reduce or eliminate use of hazardous materials on-site when practical.■ Do not over-apply fertilizers and pesticides. Prepare only the amount needed. Strictly follow the recommended usage instructions. Apply surface dressings in smaller applications, as opposed to large applications, to allow time for it to work in and to avoid excess materials being carried off-site by runoff.■ Application of herbicides and pesticides shall be performed by a licensed applicator.■ Contractors are required to complete the "Report of Chemical Spray Forms" when spraying herbicides and pesticides.■ Keep an ample supply of spill clean up material near use areas. Train employees in spill clean up procedures.■ Avoid exposing applied materials to rainfall and runoff unless sufficient time has been allowed for them to dry. |
| Maintenance and Inspections | ■ Spot check employees and subcontractors monthly throughout the job to ensure appropriate practices are being employed. |